



型号 Model	导线截面 Cable Size		最大电流 Max Current	尺寸 Dimension (mm)		
	A.W.G	mm <sup>2</sup>		Dφ	dφ	L
BN0.5(G)	26-22	0.2-0.75	9A	2.1	1.4	10.0
BN1.25(G)	22-16	0.5-1.5	19A	3.3	1.7	15.0
BN1.25(H)	22-16	0.5-1.5	19A	3.3	2.0	15.0
BN2(G)	16-14	1.5-2.5	27A	3.95	2.4	15.0
BN2(H)	16-14	1.5-2.5	27A	3.95	2.5	15.0
BN3.5(G)	12-10	2.5-4	37A	5.0	3.3	15.0
BN5.5(G)	14-12	4-6	48A	5.5	3.6	15.0
BN5.5(H)	12-10	4-6	48A	5.5	3.9	15.0
BN8(G)	#8	6-10	62A	7.0	4.8	21.0
BN14(G)	#6	10-16	88A	8.9	5.9	27.0
BN14(H)	#6	10-16	88A	8.9	6.5	27.0
BN22(G)	#4	16-25	115A	11.3	7.8	29.0
BN22(H)	#4	16-25	115A	11.0	8.4	29.0
BN38(G)	#2	35-50	160A	13.2	9.5	32.0
BN60(G)	1/0	50-70	215A	15.3	11.4	36.0
BN70(G)	2/0	70-95	235A	17.5	13.3	37.0
BN80(G)	3/0	95-120	255A	19.5	14.5	38.0
BN100(G)	4/0	120-150	300A	22.1	16.4	38.0
BN150(G)	(250/300)	150-185	395A	26.0	19.0	54.0
BN180(G)	(300/350)	185-240	440A	28.5	21.0	57.0
BN200(G)	(400/500)	240-300	470A	32.0	24.0	63.0
BN325(G)	(500/600)	300-400	650A	37.0	28.0	72.0